


H.264 x11ZS Series
DVR 411ZS-J

H.264 4CH Real-Time DVR



Main Features

- 4 Channel H.264 D1 DVR
- 4 Audio In, 2 Audio Out Support
- Main Monitor(VGA, BNC Outputs), Call Monitor (BNC Output) Support
- Triple Streaming for Live Display, Playback, and Recording
- CMS Supports E-Map
- Mac System Support
- Touch-Panel LCD Monitor Support
- 3G Mobile System Support
- HDMI for High Quality Video Output (Option)
- iPad Support



Other
Indistinct



iCATCH
Distinct



Model		411ZS-J	
Video	HDMI	1 (Option) (Video Output [1280x1024] + Audio Output)	
	Input	4	
	Output	2 BNC (1 BNC for Main monitor, 1 BNC for Co-monitor) , 1 VGA (max. 1280X1024)	
Audio	Input	4 RCA	
	Output	2 RCA	
System	Operating System	Embedded Linux OS	
	Internal HDD	Supports 1 SATA Device (HDDx1)	
	External HDD	N/A	
	Sensor In (NO, NC) Relay out	Sensor-in x 4 Relay-out x 1	
	Serial Interface	RS-485	
	USB	2 x USB2.0	
	Dimension (mm)	280(w)x51(h)x203(d)	
	Weight (w/o / HDD/DVD±RW)	1.00KG	
	Adaptor	Input 100~240V, Output 12V 3A	
	Power Source	36W	
Display	Speed	120 fps	
	Resolution (Pixel)	720 X 480(NTSC), 720 X 576(PAL)	
	Split screen	1,4, SEQ.	
	Auto Channel Switching	Switching time : 1 ~ 999 sec	
	Mode	Zoom (Digital x2~ x8), PIP, Auto SEQ.	
Recording	Compression	H.264 ASP (Internet Transmission: H.264)	
	Dual Stream Resolution (Pixel)	Main (Recording)	704 X 480, 704 X 240, 352 X 240 (NTSC) / 704 X 576, 704 X 288, 352 X 288 (PAL)
		Sub (Network)	352 x 240 (NTSC), 352 x 288 (PAL)
	Picture quality	5 levels (Highest, High, Normal, Basic, Below Basic)	
	Mode	Manual, Motion, Schedule	
	Speed	NTSC	D1 120 fps(704 x 480) / HD1 120 fps(704 x 240) / CIF 120 fps(352 x 240)
		PAL	D1 100 fps(704 x 576) / HD1 100 fps(704 x 288) / CIF 100 fps(352 x 288)
	Pre-Alarm	10 SEC	
	Post-Alarm	1 ~ 60 SEC	
	Watermark	YES	
Playback	Display	1, 4	
	Search mode	Date, time, event, camera	
	Zoom	Digital (x2 ~ x8)	
	Snapshot	YES	
	Speed	Normal, REW & FF (recorded speed x2, x4, x8, x16, x32, x64), Frame to frame, Pause	
	Device	Int. HDD	
Network	Network Interface	10/100 Ethernet	
	Protocol	TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP	
	Application	Windows XP/VISTA/7(PC Client system)	
	Remote Software	Application Software, IE Browser	
	Account	1 Admin + 10 users	
	CMS	Yes	
	Mobile	Symbian, Windows Mobile, Blackberry, iPhone, Android phone	
	Event Transport	E-mail, FTP	
Backup	Interface	USB 2.0 or SATA	
	Audio Backup	YES	
	Network	YES	
	Backup Device (Optional)	Network Backup / USB Flash Drive / USB DVD±RW	
Alarm	Motion Detection	Detected Frames: Channel	
		Sensitivity : 10 levels for each channel	
	Search (Event Criterion)	Area : Programmable individually YES	
OSD & DVR Control	Event Log	Up to the 10000 events(Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)	
	GUI	16-bit True Color	
	Multi-Language	English, Traditional Chinese, Others	
	Camera Title	Multi-Language	
	USB Mouse	YES	
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)	
	Remote Controller	IR Remote Control (Max. 1 Device)	
	System Upgrade	via USB / Network	
	Hard Key	Front Panel	
Pan / Tilt / Zoom / Control	Control From RS485 Interface(Pelco P, Pelco D, Samsung, LG, LiLin)		

H.264 x11ZS Series DVR 411ZS-J

SUBJECT CHANGED WITHOUT NOTICE

